


## AIR PEAR 25-EC

AIRIUSFANS.COM | 888-247-7327



**Housing:** ABS, UL 94 5VA flame resistance. For increased chemical resistance to oils and alkalies.

**Hardware:** Stainless steel for increased corrosion resistance.

**Motor:** 230mm, electrically commutated, thermally-protected axial motor. Operating temperature: -22°F (-30°C) to 122°F (50°C). No lubrication required, bearings are sealed.

**Power Cord:** 6 foot cord and plug provided for 100-130V fans, no plug for 200-250V.

**Control Input:** 0-10VDC.

**Stator:** Multi-vane stator significantly increases air throw for maximizing performance.

**Certification:** Conforms to UL-507, CAN/CSA-C22.2 No. 1113. ETL listed in USA and Canada.

**Safety Cable:** 6' length steel cable (fastened to body)

**Warranty:** 3 years parts and workmanship.

## Technical Specifications

Model	Input Power, 1 Ø	Amps	Watts	RPM	dB(A) <sup>1</sup>	Weight	Colors
A-25-EC-STD-100-130-(X)	100-130VAC, 60Hz	0.46	31	1640	44, 42, 40	9 lbs.	X = Off white (W) or black (B)
A-25-EC-STD-200-250-(X)	200-250VAC, 60Hz	0.26	30	1700	44, 42, 40	9 lbs.	X = Off white (W) or black (B)
A-25-EC-SH-100-130-(X)	100-130VAC, 60Hz	0.46	31	1640	44, 42, 40	7 lbs.	X = Off white (W) or black (B)
A-25-EC-SH-200-250-(X)	200-250VAC, 60Hz	0.26	30	1700	44, 42, 40	7 lbs.	X = Off white (W) or black (B)

(1) Calculated sound pressure at 15, 20 and 25 foot distances based on non-reflective area. 69 dB(A) Sound Power Level, designed to meet ISO 3744 - engineering grade precision for determining sound power. Data independently verified by third party. Tests performed in-unit.

## Controls & Factory Installed Options

Item	Description
Pearlink-F	Pearlink Fan Sensor- One Per Fan. Wi-Fi iOS/Android App based controller. Factory installed option.
Pearlink-T	Pearlink wired (120v) Floor Thermostat- One Per Room
POT-1	Wall-mounted speed control. Low voltage control wiring daisy-chained between fans to be controlled as a group.
AiriusBAC24	BACnet MS/TP card for integration with an existing BACnet system. Individually control speed, on/off and monitor fan status.
GUARD25	Intake grille: Phosphated steel coated in black plastic. Factory installed option.
DeltaT-EC-Pack	Includes wall mounted control interface, two temperature sensors and 24VDC power supply. 0-10VDC output.

<b>Model:</b>	X = Off white (W) or black (B)	<b>Qty:</b>
Controls/Options:		Qty: